

# TXH GTAW Torches

TXH-121, 151, 201, 251, 401



- TXH torches are designed to provide the utmost in convenience, versatility, and ergonomics to the welder
- Choose between air-cooled and water-cooled versions, with or without gas valve, and with or without a flexible neck to suit specific applications
- The torch heads are manufactured with high temperature resistant silicone rubber insulation
- All copper components ensure cooler running temperatures and maximum current capacity
- Integrated dual soft grips ensure the handle remains in place with minimal grip pressure
- Positioning of the torch is made easier by the combination of knuckle joints and a flexible leather section covering the first 31.5 in. (800 mm) of the torch immediately behind the handle

Specifications						
	TXH-121	TXH-151	TXH-201	TXH-251w	TXH-401w	TXH-401w HD
Permitted load at: 35% duty cycle 60% duty cycle 100% duty cycle	- 120A 100A	150A 120A 100A	200A 150A 140A	- 250A 200A	400A 350A 300A	430A 400A -
Ø in. (mm)	.040-1/8 in. (1.0-3.2 mm)	.040-1/8 in. (1.0-3.2 mm)	.040-5/32 in. (1.0-4.0 mm)	.040-1/8 in. (1.0-3.2 mm)	.040-3/16 in. (1.0-4.8 mm)	.040-3/16 in. (1.0-4.8 mm)

Ordering Information			
Air-Cooled Torches – OKC25 Connector [1 in. (25 mm)]		Air-Cooled Torches – OKC50 Connector [2 in. (50 mm)]	
TXH-121, 13 ft. (4 m) <sup>1</sup>	0700300522	TXH-121, 13 ft. (4 m)	0700300524
TXH-121, 13 ft. (4 m)	0700300532	TXH-121, 26 ft. (8 m)	0700300529
TXH-121, 26 ft. (8 m) <sup>1</sup>	0700300527	TXH-121F, 13 ft. (4 m)	0700300526
TXH-121, 26 ft. (8 m)	0700300534	TXH-121F, 26 ft. (8 m)	0700300531
TXH-121V, 13 ft. (4 m)	0700300523	TXH-151, 13 ft. (4 m)	0700300538
TXH-121V, 26 ft. (8 m)	0700300528	TXH-151, 26 ft. (8 m)	0700300544
TXH-121F, 13 ft. (4 m)	0700300525	TXH-151V, 13 ft. (4 m)	0700300539
TXH-121F, 26 ft. (8 m)	0700300530	TXH-151V, 26 ft. (8 m)	0700300545
TXH-151, 13 ft. (4 m) <sup>1</sup>	0700300538	TXH-151F, 13 ft. (4 m)	0700300541
TXH-151, 13 ft. (4 m)	0700300548	TXH-151F, 26 ft. (8 m)	0700300547
TXH-151, 26 ft. (8 m)	0700300550	TXH-201, 13 ft. (4 m)	0700300552
TXH-151, 26 ft. (8 m) <sup>1</sup>	0700300542	TXH-201, 26 ft. (8 m)	0700300555
TXH-151V, 13 ft. (4 m)	0700300537	TXH-201V, 13 ft. (4 m)	0700300553
TXH-151V, 26 ft. (8 m)	0700300543	TXH-201V, 26 ft. (8 m)	0700300556
TXH-151F, 13 ft. (4 m)	0700300540	TXH-201F, 13 ft. (4 m)	0700300554
TXH-151F, 26 ft. (8 m)	0700300546	TXH-201F, 26 ft. (8 m)	0700300557
TXH-201, 13 ft. (4 m)	0700300588		
TXH-201, 26 ft. (8 m)	0700300560		
TXH-201F, 13 ft. (4 m)	0700300599		
Water-Cooled Torches – OKC50 Connector [2 in. (50 mm)]			
TXH-251w, 13 ft. (4 m)	0700300561	TXH-401w, 13 ft. (4 m)	0700300565
TXH-251w, 26 ft. (8 m)	0700300563	TXH-401w, 26 ft. (8 m)	0700300567
TXH-251wF, 13 ft. (4 m)	0700300562	TXH-401w HD, 13 ft. (4 m)	0700300566
TXH-251wF, 26 ft. (8 m)	0700300564	TXH-401w HD, 26 ft. (8 m)	0700300568
Remote Control Torches – OKC50 Connector [2 in. (50 mm)]			
TXH-121r, 13 ft. (4 m)	0700300620	TXH-201Fr, 26 ft. (8 m)	0700300631
TXH-121r, 26 ft. (8 m)	0700300622	TXH-251wr, 13 ft. (4 m)	0700300632
TXH-121Fr, 13 ft. (4 m)	0700300621	TXH-251wr, 26 ft. (8 m)	0700300634
TXH-151r, 13 ft. (4 m)	0700300624	TXH-251wFr, 13 ft. (4 m)	0700300633
TXH-151r, 26 ft. (8 m)	0700300626	TXH-251wFr, 26 ft. (8 m)	0700300635
TXH-151Fr, 13 ft. (4 m)	0700300625	TXH-401wr, 13 ft. (4 m)	0700300636
TXH-151Fr, 26 ft. (8 m)	0700300627	TXH-401wr, 26 ft. (8 m)	0700300638
TXH-201r, 13 ft. (4 m)	0700300628	TXH-401wr HD, 13 ft. (4 m)	0700300637
TXH-201r, 26 ft. (8 m)	0700300630	TXH-401wr HD, 26 ft. (8 m)	0700300639
TXH-201Fr, 13 ft. (4 m)	0700300629		

<sup>1</sup>OKC25C F = Flexible. V = Gas Valve.