

# LYNX



## Welding inverter WMEM 180

WMEM 180 is equipped with:

- Compact and portable inverter for MMA welding
- Durable and impact resistance design
- Easy to operate - only current setting needed
- Digital Ampere meter shows the welding current
- Welds most electrodes from ø 1,6 - 4,0 mm
- Capable to work on generator power source
- Over current protection / Over voltage protection
- Automatic hot start
- Automatic arc force
- Automatic anti-stick function

### TECHNICAL DATA

Order No. ....	0301803502
MAIN SUPPLY (V/Ph Hz) .....	230V 50HZ
Input Voltage Tolerance (%) .....	±15
Input power (kVA).....	7,8
SETTING RANGE (A).....	20-180
MAX. OUTPUTS AT 20% DUTY CYCLE, A (MMA).....	180
MAX. OUTPUTS AT 60% DUTY CYCLE, A (MMA).....	104
MAX. OUTPUTS AT 100% DUTY CYCLE, A (MMA).....	80
MAX. OUTPUTS AT 20% DUTY CYCLE, A (TIG).....	180
MAX. OUTPUTS AT 60% DUTY CYCLE, A (TIG).....	104
MAX. OUTPUTS AT 100% DUTY CYCLE, A (TIG).....	80
Open-circuit voltage.....	82
Maximum current draw (IEFF) .....	15.2
Electrode Sizes Dia.....	1.6-4.0
DIMENSIONS (mm).....	420x154x296
WEIGHT of the machine (kg).....	4.76



### STANDARD EQUIPMENT:

- welding cable
- returne cable